

DS-7700NI-I4/P SERIES NVR



Features and Functions

Professional and Reliable

- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected

Video Input and Transmission

- Up to 32-ch 12 MP IP cameras can be connected
- Connectable to the third-party network cameras

Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel recording at up to 12MP resolution

HD Video Output

- HDMI and VGA independent outputs provided
- HDMI Video output at up to 4K (3840 × 2160) resolution

Storage and Playback

- Up to 4 SATA interfaces connectable for HDD connection
- Smart search for efficient playback
- 8/16-ch synchronous playback at up to 1080p resolution
- Normal/Important/Custom video playback

Important files management

HDD health monitoring

Smart & POS Function

- Supports multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- Supports VCA search for fire/ship/temperature/temperature difference detection triggered video files

POS information overlay on live view and playback

POStiggered recording and alarm

Network & Ethernet Access


- Hik-Connect for easy network management
- Gigabit Ethernet network interface
- 8/16 independent PoE network interfaces are provided
- Long distance (100-300 m) network transmission via PoE



Specifications

Model		DS-7708NI-I4/8P	DS-7716NI-I4/16P	DS-7732NI-I4/16P		
Video/Audio input	IP video input	8-ch Up to 12 MP resolution	16-ch	32-ch		
	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)				
	Network	Incoming bandwidth Outgoing bandwidth Remote connection	80 Mbps 256 Mbps 32	160 Mbps 256 Mbps 128		
Video/Audio output	Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4AF /DCAF/2AF/AF/QAF				
	CVBS output (Optional)	1-ch, BNC(1.0 Vp-p, 75 Ω), resolution PAL 704 × 576, NTSC 704 × 480				
	HDMI output resolution	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz				
	VGA output resolution	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz				
	Audio output	1-ch, RCA (Linear, 1 kΩ)				
Decoding	Decoding format	H.265/H.265+/H.264/H.264+/MPEG4				
	Live view / Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4AF /DCAF/2AF/AF/QAF				
	Synchronous playback	8-ch	16-ch	16-ch		
	Capability	2-ch @ 12 MP (20fps) / 4-ch @ 8 MP (25fps) / 8-ch @ 4MP (30fps) / 16-ch @ 1080p (30fps)				
Network management	Network protocols	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS				
Hard disk	SATA	4 SATA interfaces for 4HDDs				
	Capacity	Up to 8TB capacity for each HDD				
External interface	Network interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface				
	Serial interface	1 RS-485 (half-duplex), 1 RS-232				
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0				
	Alarm in/out	16/4				
POE Interface	Interface	8 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces			
	Power	≤200W				
	Supported standard	IEEE 802.3 af/at				
General	Power supply	100 to 240 VAC				
	Power	≤300 W				
	Consumption (without hard disk)	≤20 W (without enabling PoE)				
	Working temperature	-10 to +55° C (+14 to +131° F)				
	Working humidity	10 to 90 %				
	Chassis	19-inch rack-mounted 1.5U chassis				
	Dimensions (W × D × H)	445 × 400 × 71 mm (17.5" × 15.7" × 2.8")				

Physical Interfaces



Index	Description	Index	Description
1	LAN1 and LAN2 Interfaces	7	VGA Output (DB9 Connector)
2	AUDIO OUT	8	RS485 Serial Interface
3	AUDIO IN	9	Controller Port, Alarm In/Alarm Out
4	HDMI Interface	10	GND
5	USB 3.0 Interface	11	100 to 240 VAC power supply
6	RS-232 Serial Interface	12	Power Switch
13	Network Interfaces with PoE function (8 interfaces for DS-7708NI-I4/8P and 16 interfaces for DS-7716NI-I4/16P and DS-7732NI-I4/16P.)		

Available Models

DS-7708NI-I4/8P, DS-7716NI-I4/16P, DS-7732NI-I4/16P

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision Russia
T +7-495-669-67-99
salerau@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Latam
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com